

Sentinel X100

Inhibitor for Hydronic Heating Systems

Features & Benefits

- Effectively controls scale and corrosion
- Helps prevent the formation of hydrogen gas
- Helps prevent boiler noise
- Suitable for all metals including aluminum
- Easy to handle
- Non-toxic and biodegradable
- Concentration is easily checked with a Sentinel Test Kit or a conductivity meter
- Manufactured under a quality system conforming to ISO9001



Sentinel Test Kit

Simply take a sample of water from the system, add the test tablets and shake. After 5 minutes compare the colour with the panel. Each kit contains sufficient tablets for 10 tests.

Applications

Sentinel X100 has been formulated as a multipurpose treatment to inhibit corrosion, scale, boiler noise and hydrogen gassing in all types of indirect heating systems including those containing aluminum components.

Sentinel X100 is suitable for use in all waters, both hard and soft. The formulation is completely non-toxic.

Dosing & Feeding

1 Quart of Sentinel X100 is sufficient to treat a typical residential system of 25 Gallons. Larger systems should be dosed at 1% of system water.

For best results, systems should be cleaned and flushed with clean make-up water. New systems and those up to 6 months old with Sentinel X300, existing systems with Sentinel X400. If the system is already noisy due to limescale deposits in the heat exchanger, Sentinel X200 should be added together with Sentinel X100.

Open Systems: Dose via F&E cistern, via a bypass feeder or use a dosing vessel.

Sealed Systems: If the system is empty, add to any convenient point before filling. If full, use a dosing vessel to inject via the filling loop or other access point.

Physical Properties

- Appearance: Clear colourless to pale green or pale yellow liquid
- Odor: Mild
- Specific gravity: 1.10 (68°F)
- pH (concentrate): 6.5 (approx)
- Freezing point: 27.5°F

Packaging

- 1 Quart bottle
- 1 Gallon drum
- 5 Gallon drum

Safety Precautions

The information provided overleaf enables compliance with the Control of Substances Hazardous to Health Regulations. A full Safety Data Sheet is available upon request.

Sentinel X100

Inhibitor for Hydronic Heating Systems	An aqueous solution of inorganic and organic corrosion and scale inhibitors.
Health Hazards	Not for use in potable water systems. This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). CAUTION: May cause eye, skin, and respiratory tract irritation
Handling	Avoid contact with skin and eyes. Keep out of reach of children and animals. Wash out empty container thoroughly with water before disposal.
Storage	Keep container tightly closed. Store in cool, well ventilated area.
Spillage	Flush spillage with plenty of water and wash to waste.
Fire/Explosion Risks	Non-flammable
First Aid	Skin Exposure : Wash immediately with plenty of water. If irritation develops, seek medical attention. Eye Exposure : Flush immediately with plenty of running water. Keep eyelids apart. Seek medical advice. Ingestion : Rinse mouth with water. Do NOT induce vomiting! Seek medical advice.